



Industrial Gas Solutions  
by Macurco

TracXP is the industrial products division of Macurco Gas Detection, who has been providing gas detection solutions for over 50 years. The TracXP line addresses special hazard applications including harsh industrial environments and hazardous locations with a comprehensive line of wired and wireless gas detection solutions.



## TXP-C20 & TXP-C40

### 2 and 4 Channel Alarm Control Panels

The TracXP C20 and TracXP C40 are versatile control panels that provide signal conditioning, display and alarm functions for up to four input channels. Both control panels come standard with two programmable relays. A large graphic LCD screen displays engineering units, 30-minute trends or bar-graphs. Status indicating Yellow and Red LED's provide highly visible real time alarm status and three adjustable alarm levels per channel. Versatile input options include 4-20 mA inputs or combinations of bridge (Catalytic Bead/IR) and toxic (Electrochemical) sensors. Output options include 4-20 mA, Modbus® RTU, dual Ethernet Modbus® TCP bridge, and additional relay outputs.



TXP-C20  
Poly Enclosure



TXP-C40  
Poly Enclosure

### Key Features

- NEMA 4X enclosure
- LCD readout displays engineering units, bar graphs or 30 minute trends
- LED's indicate alarm and fault status
- 2 programmable SPDT relays for warning, high alarm, horn and fault conditions
- RS-485 Modbus® serial port
- 6 programmable 5A relays (optional)
- "Cal Mode" offers pushbutton zero and span calibration for direct sensor input applications

### Applications

- Oil & Gas
  - Upstream
  - Mid-stream
  - Downstream
- Refining & chemical production
- Water / waste water treatment plants
- Food & beverage facilities
- Metal manufacturing
- Pulp & paper
- Power generation

# TXP-C20 & TXP-C40

## Specifications

### Controller Specifications

Enclosure Size	14.1"(L) x 12.14"(W) x 7.75"(H) Poly Enclosure
Shipping Weight	12 lbs. (5.4 k.) Poly Enclosure
Power Supply	120 - 240 VAC / 10 - 30 VDC, 50 watt primary power supply (Standard)
Inputs	<p>TXP-C20:</p> <p>Dual bridge (Catalytic Bead/IR)</p> <p>Dual toxic (Electrochemical)</p> <p>One bridge and one toxic</p> <p>Dual 4-20 mA input</p> <p>TXP-C40:</p> <p>Quad bridge (Catalytic Bead/IR)</p> <p>Quad toxic (Electrochemical)</p> <p>Dual bridge and dual toxic</p> <p>Dual bridge and dual 4-20 mA</p> <p>Quad 4-20 mA</p>
Relays	<p>Two programmable 5A 30 VDC or 250 VAC resistive Form C Relays</p> <p>Programmable 5A 30 VDC or 250 VAC resistive Form C Relays (Option)</p>
Serial Port Option	<p>TXP-C20:</p> <p>Modbus® RTU Slave RS-485 Port Tx / Rx LED's</p> <p>TXP-C40:</p> <p>Modbus® RTU Master/Slave RS-485 Port Tx / Rx LED's</p> <p>Serial to dual Ethernet Modbus® TCP bridge, for C1D2 locations</p>
Display	<p>Graphic 128 x 64 pixel backlit LCD indicates engineering units, trends or bar-graphs.</p> <p>Six LED's provide alarm status, cal mode and keypad activity</p>
Temperature	-13°F to 140°F (-25°C to +60°C)
Approvals	CSA C22.2 No. 1010.1 and C22.2 NO 152 for combustible gases and ISAS82.02: UL1604 / C22.2 No 213 (NEMA 4X Enclosures: Div. 2, Groups A, B, C & D EN55011 and EN 61000)

Represented By:

## TXP-C20 Parts & Accessories\*

### Part Number Description

88-C020-0000-20	Power Supply, 100-240 VAC / 10-30 VDC w/50W, C1, D2
90-8000-0000-07	LCD / micro controller PCB & ribbon cable
88-4000-0020-00	Optional Alarm Relay Board (6, 5A Form C Relays)
88-4000-0070-00	Dual 4-20 mA output board
88-5000-0080-00	RS-232 / RS-485 RTU addressable interface
88-4000-0300-00	Dual channel 4-20 mA input board
88-4000-0400-00 1	Bridge sensor, 1 EC sensor input combo board


## TXP-C40 Parts & Accessories\*

### Part Number Description

88-C020-0000-20	Power Supply, 100-240 VAC / 10-30 VDC w/50W, C1, D2
90-8000-0000-09	Quad LCD / micro controller PCB & ribbon cable
88-4000-0020-00	Alarm relay board (6, 5A form C relays)
88-5000-0060-00	Single RS-485 serial Modbus® TCP bridge, non-hazardous locations
88-5000-0070-00	Quad channel 4-20 mA output board
88-5000-0070-20	Serial to dual Ethernet Modbus® TCP bridge, for C1D2 locations
88-5000-0080-00	RS-232 / RS-485 RTU addressable interface
90-8000-5000-00	Quad channel 4-20 mA input board
90-8000-6000-00	(2) Bridge Sensors and (2) 4-20 mA or (4) Bridge sensors input boards

\*For additional options please contact your TracXP representative

## Enclosure Dimensions



**Macurco Inc.**  
1504 W. 51st Street  
Sioux Falls, SD 57105

Phone: 1-877-367-7891

Macurco Inc. All rights reserved.

**AirSafety™**  
PORTABLE GAS DETECTION SOLUTIONS

**Macurco™**  
Buildings & Home Solutions

**TracXP™**  
INDUSTRIAL GAS SOLUTIONS



Website: [www.macurco.com](http://www.macurco.com)

Email: [info@macurco.com](mailto:info@macurco.com)