



Industrial Gas Solutions  
by Macurco

# TXP-T40

Fixed Single or Dual Sensor Gas Monitor



TXP-T40  
Aluminum Housing



TXP-T40  
Poly Housing



TXP-T40  
Aluminum Dual Sensor



The TracXP T40 transmitter is a highly configurable fixed gas detector supporting single or dual sensor applications in Class 1 Division 1 or Class 1 Division 2 environments. Local and remote sensor options allow the T40 to adapt to a wide variety of industrial applications. TracXP intelligent sensors simplify sensor installation and configuration by transferring sensor information to the transmitter including sensor type, measurement range, calibration span values, last calibration date, serial number, and manufacture date. A vivid status indicating color display and LED notification provide superior visual verification of safe or unsafe conditions. Intuitive non-intrusive magnetic interface and embedded webpage make setting up and programming easy. Aluminum, Non-metallic (Poly), and Stainless-Steel enclosures provide alternatives to meet a wide variety of application and cost requirements.

## Key Features

- Certified for Class 1, Div 1 or Div 2
- Vivid QVGA backlit color TFT display
- Displays gas values, units of measurement, trend graphs and alarm levels
- LED alarm statues indication
- Dual sensor capable
- Supports remote sensor applications
- Embedded webpage via ethernet port
- 4 configurable 5A relays
- Modbus® TCP/IP output

## Applications

- Oil & Gas
- Pipeline compression
- Refining & chemical production
- Water / waste water treatment plants
- Food & beverage facilities
- Metal manufacturing
- Pulp & paper
- Power generation
- General industry

# TXP-T40

## Specifications

### Detector Specifications

Size	5"(L) x 5.4"(W) x 8"(H) 4"(L) x 5"(W) x 7"(H)	Aluminum Housing Poly Housing
Shipping Weight	6.5 lbs. (3 k.) 3 lbs. (2 k.)	Aluminum Housing Poly Housing
Power Supply	10-30 VDC at < 10 watts with relay board (all relays energized)	
Input	Two Sensor Channels; combination of electrochemical, catalytic bead, infrared or PID	
Standard Output	Dual 3-wire 4-20mA current source, Modbus® TCP/IP via ethernet RJ-45 connector	
Optional Output	Three programmable relays plus dedicated FAULT relay Dual programmable master / slave Modbus® RS-485 serial interfaces	
Display	QVGA backlit color TFT 320x240	
Temperature	-40°F to 140°F (-40°C to +60°C) *See Sensor Limitations	
Humidity	IR Sensor: RH Non-condensing 95% Electrochemical Sensor: RH Non-condensing 85%	
IP Rating	Cast Aluminum Enclosure: IP65; IP66 w/ 88-C50G-0000-00 Black Poly Enclosure: Suitable for IP54	
Approvals	Cast Aluminum Enclosure: Explosion-Proof Cl.1 Div.1 Gr ABCD w/88-C200-0002-00 Sensor Housing Non-Incendive Cl.1 Div.2 Gr ABCD w/ 88-C200-0003-00, 30-0062-2200-1 · Cal Kit, .5 LPM Reg (M), Tubing, Wands, Case Sensor Housing CSA Black Poly Enclosure: Non-Incendive Cl.1 Div.2 Gr ABCD**	

### Represented By:

## Sensor Options\*

### Gas Options

Acetylene (C <sub>2</sub> H <sub>2</sub> )	Methane (CH <sub>4</sub> )
Ammonia (NH <sub>3</sub> )	Methyl Mercaptan (CH <sub>3</sub> SH)
Benzene (C <sub>6</sub> H <sub>6</sub> )	Nitric Oxide (NO)
Carbon Dioxide (CO <sub>2</sub> )	Nitrogen Dioxide (NO <sub>2</sub> )
Carbon Monoxide (CO)	Oxygen (O <sub>2</sub> )
Chlorine (Cl <sub>2</sub> )	Ozone (O <sub>3</sub> )
Chlorine Dioxide(ClO <sub>2</sub> )	Propane (C <sub>3</sub> H <sub>8</sub> )
Combustibles (LEL & VOL)	Refrigerants (Various)
Hydrogen (H <sub>2</sub> )	Sulfur Dioxide (SO <sub>2</sub> )
Hydrogen Chloride (HCl)	Sulfur Hexafluoride (SF <sub>6</sub> )
Hydrogen Fluoride (HF)	Volatile Organic Compounds (VOCs)
Hydrogen Sulfide (H <sub>2</sub> S)	

## Accessories\*

### Part Number      Description

88-1109-0000-10	Remote Sensor Assembly, Aluminum, S.S. Sensor Head C1D1 (Non-reactive Sensor)
88-1109-0000-20	Remote Sensor Assembly, Aluminum, S.S. Sensor Head C1D2 (Reactive Sensor)
88-1309-0000-30	Remote Sensor Assembly, Poly C1D2 Non-Incendive
88-1000-0040-00	Relay Option Board (4) 5A/Dual Modbus® (Master/Slave)
88-C20S-0000-00	Sensor Head Flow Cell Adapter <sup>1</sup>
88-C50G-0000-00	Splash Guard W/Calibration Port <sup>1</sup>
88-C200-0000-0C	Duct Mount Kit (AL or SS)
88-C200-0000-0D	Duct Mount Kit (Poly)
88-C50I-0000-00	Sensor Head Cal-Adapter <sup>1</sup>
88-C000-0000-02	Large Magnetic Wand, AL/SS Transmitters
88-C000-0000-01	Small Magnetic Wand, Poly Transmitters
30-0062-2200-1	Cal Kit, .5 LPM Reg (M), Tubing, Wands, Case

<sup>1</sup> Compatible with Stainless Steel Sensor Housing / <sup>2</sup> Compatible with Poly Sensor Housing

\*Please contact your TracXP representative for additional gas type, sensor range, and accessories

\*\*Excludes Catalytic Bead sensors

Macurco Inc.

1504 W. 51st Street  
Sioux Falls, SD 57105

Phone: 1-877-367-7891

Macurco Inc. All rights reserved.

**AimSAFETY™**  
PORTABLE GAS DETECTION SOLUTIONS

**Macurco™**  
BUILDING & HOME SOLUTIONS

**TracXP™**  
INDUSTRIAL GAS SOLUTIONS



Website: [www.macurco.com](http://www.macurco.com)

Email: [info@macurco.com](mailto:info@macurco.com)

11/2025